

When it comes to maximize
your return on investment, think

Coaxcyl EM



Coaxcyl EM

features and benefits:


1. Honeycomb based structure, for consistent print results & easy handling
2. Dampening function built-in to reduce press bounce
3. Designed to last long
4. Smooth installation on press & quick make ready



Durable End Cap



Durable & precise
registration
Aluminum insert



Cutting guide
Ceramic based

Axcyl

Technical data

Application	Hard pneumatic plate mounting sleeve
Ink system	Compatible with all Flexo inks (solvent based, water based and UV)
Tapes	Compatible with all market tapes used in plate mounting
Tolerance on Outer Diameter	Nominal +/- 20µm
Tolerance on TIR	20µm
Surface	Extremely durable Epoxy & technical fabrics
Utilisation Temperature range	20°C to 45°C
Wall thickness range	From 4 to 100mm
Width range	From 500 to 2000mm
Stork Diameter range	From 60 to 400mm
Conductive	Fulfill ATEX 95 requirements when required
Air supply	6 bars @ minimum 12l/sec
Cleaning	Any solvent compatible with UV, solvent, and water-based inks
Storage	Vertical / Horizontal indifferent

Axyl plate mounting sleeves for narrow and wide web printing presses help flexo printers enhancing and improving performance, in efficient and sustainable way.

CONTACT SIMONAZZI



Tel. +39 02-95749073 +39 02-95749074

www.simonazzi.it
email to job@simonazzi.it